

# CSS Magnum Plus

## Produits frais ou congelés. Plus c'est froid, mieux c'est

- Température la plus basse
- Descente en température rapide
- Contrôle précis de la température
- Faible consommation énergétique
- Technologie éprouvée et conception simple
- Service après-vente mondial

### DONNÉES TECHNIQUES

Débit d'air		Caractéristiques	
Type de groupe frigorifique	High capacity Refrigeration unit for installation in 10, 20, 40 or 45 ■ containers for stationary applications. All Aluminum "Picture frame" R-404A or R-452A Refrigerant. Charge 4.0 kg (8.8 lbs) Copeland Scroll compressor. Emerson MP4000 controller	Circulation d'air frais	Unit allow fresh air exchange to cargo area. Using: Rotating disk in 0-100 m <sup>3</sup> /h. And hinged door for 100 m <sup>3</sup> /h, 150 m <sup>3</sup> /h, 175 m <sup>3</sup> /h, 215 m <sup>3</sup> /h, or 225 m <sup>3</sup> /h. Optional to get sensor and log in datalogger.
Fuite de chaleur requise de la caisse	42 Watt/°K @ 20C wall temperature, to ensure set-point at ambient	Niveau sonore	Soundpower per ISO 3744:2010) is 90.1 dB(A) with set-point -30°C running 400V/50 Hz. 94.9dB(A) with set-point -30°C running 400V/60 Hz.
Protection des conteneurs	Pressure equalization valve (1400 Pascal / 140 mm WG) to avoid excessive vacuum in the container	Certifications et normes de conception	ISO1496-2 CE Pharma GDP AHRI ATO (former Sprenger Institute) ATP American Bureau of Shipping, Lloyds and Bureau Veritas
Plage de sélection du point de consigne	-40°C to +30°C (-40°F to 86°F)		

## MARINE

Plage de températures ambiantes	-30°C to +50°C (-22°F to 122°F)
---------------------------------	------------------------------------

	USDA TIR (International Customs Regulations for Containers)
--	--

Puissance frigorifique à la température ambiante de +37,8 °C (100 °F)	
Au point de consigne +21,1 °C (70 °F)	16,500 watt @ 460V/60Hz 14,220 watt @ 400V/50Hz
Au point de consigne +1,7 °C (35 °F)	11,900 watt @ 460V/60Hz 10,260 watt @ 400V/50Hz
Au point de consigne -17,8 °C (0 °F)	7,200 watt @ 460V/60Hz 6,210 watt @ 400V/50Hz
Au point de consigne -28,9 °C (-20 °F)	5,000 watt @ 460V/60Hz 4,310 watt @ 400V/50Hz
Au point de consigne -40 °C (-40 °F)	3,700 watt @ 460V/60Hz 3,190 watt @ 400V/50Hz
Puissance calorifique maximale	5,250 watt @ 460V/60Hz

Électricité	
Alimentation électrique	A/C 400 to 500 Volt 3 phase 60 Hz ±2,5% A/C 360 to 460 Volt 3 phase 50 Hz ±2,5%
Disjoncteur principal	25 Amp
Câble d'alimentation	18.3 m (60 LF) cable (4phase and ground) with CEE17 power plug (32 Amp; ground 3h). Control box is equipped with a 3 m cable 230V/16 Amp 3 phase power plug to provide output for light, man-trap alarm
Réchauffeurs pour le mode Dégivrage / Chauffage	3 * 1,360 watt electrical resistance heaters. Optional to get 3*2,000 watt heater, and allow cargo temperature +40C

Contrôleur	
Généralités	Advanced Microprocessor MP4000 Emerson Controls Temperature control using 5 PT1000 sensors and 1 NTC for compressor. Main control temperature sensors

for Supply and Return air are PT1000 Class A per EN60751:2008 i.e. with accuracy of +/-0.15°C (+/- 0.27°F) Temperature accuracy in "non-optimized energy savings mode": Chilled temperature +/-0.25°C (+/-0.45°F) Frozen temperature set-points: +/-1°C (+/-1.8°F) Datalogger document system parameters and changes, results of Pre-Trip Inspections, Alarms & messages, as well as temperature logs. Temperature logs are defaulted to 1 hour interval, and user can change to other interval. Datalogger memory allow 15,000 temperature logs When power is disconnected, datalogger continue to log temperatures for 120 logs (3 days \* 24 hr interval). 4

## MARINE

USDA cargo sensor ports with Deutsch receptacles (Option supply of 15m (49 LF) long cables with NTC sensor (accuracy +/- 0.15°C (+/-0.27°F)) Telematics (option) to allow two-way communication with controller. Using Global Network Satellite System and Global cellular LTE, 2G, 3G signal) Datalogger can be retrieved via serial port on unit, via SD-card or via Telematics Controller continuously monitor health of system and components, an early indication can trigger a "message" and a critical issues trigger an "alarm" Unit controller has LED that flash red if "Alarm" is active Defrost: To melt ice entering with cargo, and/or from door openings electrical defrost

## MARINE

heaters are installed with capacity 4,080 watt @ 460/60Hz and 3,520 watt @ 400V/50Hz.

Defrost activates after 2 hour, after that controller monitor coil temperature, and allow upto 48 hour before a timed defrost. Controller monitor between evaporator coil sensor and return air sensor.

Dehumidification:  
Humidity in cargo area can be controlled between 50 and 98 rH%.

This is controlled by re-heating the evaporator air with the defrost heaters.

Accuracy at rH set-point: 50% to 75%:  
+/-1.5% 75% to 95%:  
+/-3.0%