

CSS Magnum Plus

Для свежих или замороженных продуктов. Чем быстрее, тем лучше

- Самая низкая температура
- Быстрый выход на режим
- Точное регулирование температуры
- Низкое энергопотребление
- Проверенная технология и простая конструкция
- Глобальная сеть обслуживания

ТЕХНИЧЕСКИЕ ДАННЫЕ	
Расход воздуха	Характеристики
Тип установки	High capacity Refrigeration unit for installation in 10, 20, 40 or 45 ■ containers for stationary applications . All Aluminum "Picture frame" R-404A or R-452A Refrigerant. Charge 4.0 kg (8.8 lbs) Copeland Scroll compressor. Emerson MP4000 controller
Требуемый теплоприток кузова	42 Watt/°K @ 20C wall temperature, to ensure set-point at ambient
Защита контейнеров	Pressure equalization valve (1400 Pascal / 140 mm WG) to avoid excessive vacuum in the container
Диапазон заданных значений set point	-40°C to +30°C (-40°F to 86°F)
	Unit allow fresh air exchange to cargo area. Using: Rotating disk in 0-100 m3/h. And hinged door for 100 m3/h, 150 m3/h, 175 m3/h, 215 m3/h, or 225 m3/h. Optional to get sensor and log in datalogger.
	Soundpower per ISO 3744:2010) is 90.1 dB(A) with set-point -30°C running 400V/50 Hz. 94.9dB(A) with set-point -30°C running 400V/60 Hz.
	Сертификация и стандарты проектирования
	ISO1496-2 CE Pharma GDP AHRI ATO (former Sprenger Institute) ATP American Bureau of Shipping, Lloyds and Bureau Veritas

MARINE

Диапазон температур окружающей среды	-30°C to +50°C (-22°F to 122°F)
--------------------------------------	------------------------------------

	USDA TIR (International Customs Regulations for Containers)
--	--

Холодопроизводительность	
При температуре окружающей среды +37,8 °C	
При заданном значении set point +21,1 °C	16,500 watt @ 460V/60Hz 14,220 watt @ 400V/50Hz
При заданном значении set point +1,7 °C	11,900 watt @ 460V/60Hz 10,260 watt @ 400V/50Hz
При заданном значении set point -17,8 °C	7,200 watt @ 460V/60Hz 6,210 watt @ 400V/50Hz
При заданном значении set point -28,9 °C	5,000 watt @ 460V/60Hz 4,310 watt @ 400V/50Hz
При заданном значении set point -40 °C	3,700 watt @ 460V/60Hz 3,190 watt @ 400V/50Hz
Максимальная теплопроизводительность	5,250 watt @ 460V/60Hz

Электричество	
Блок питания	A/C 400 to 500 Volt 3 phase 60 Hz ±2,5% A/C 360 to 460 Volt 3 phase 50 Hz ±2,5%
Главный автоматический выключатель	25 Amp
Кабель питания	18.3 m (60 LF) cable (4phase and ground) with CEE17 power plug (32 Amp; ground 3h). Control box is equipped with a 3 m cable 230V/16 Amp 3 phase power plug to provide output for light, man-trap alarm
Нагреватели для режима оттайки/нагрева	3 * 1,360 watt electrical resistance heaters. Optional to get 3*2,000 watt heater, and allow cargo temperature +40C

Контроллер	
Общие сведения	Advanced Microprocessor MP4000 Emerson Controls Temperature control using 5 PT1000 sensors and 1 NTC for compressor. Main control temperature sensors

for Supply and Return air are PT1000 Class A per EN60751:2008 i.e. with accuracy of +/-0.15°C (+/- 0.27°F) Temperature accuracy in "non-optimized energy savings mode": Chilled temperature +/-0.25°C (+/-0.45°F) Frozen temperature set-points: +/-1°C (+/-1.8°F) Datalogger document system parameters and changes, results of Pre-Trip Inspections, Alarms & messages, as well as temperature logs. Temperature logs are defaulted to 1 hour interval, and user can change to other interval. Datalogger memory allow 15,000 temperature logs When power is disconnected, datalogger continue to log temperatures for 120 logs (3 days * 24 hr interval). 4

MARINE

USDA cargo sensor ports with Deutsch receptacles (Option supply of 15m (49 LF) long cables with NTC sensor (accuracy +/- 0.15°C (+/-0.27°F)) Telematics (option) to allow two-way communication with controller. Using Global Network Satellite System and Global cellular LTE, 2G, 3G signal) Datalogger can be retrieved via serial port on unit, via SD-card or via Telematics Controller continuously monitor health of system and components, an early indication can trigger a "message" and a critical issues trigger an "alarm" Unit controller has LED that flash red if "Alarm" is active Defrost: To melt ice entering with cargo, and/or from door openings electrical defrost

MARINE

heaters are installed with capacity 4,080 watt @ 460/60Hz and 3,520 watt @ 400V/50Hz.

Defrost activates after 2 hour, after that controller monitor coil temperature, and allow upto 48 hour before a timed defrost. Controller monitor between evaporator coil sensor and return air sensor.

Dehumidification:
Humidity in cargo area can be controlled between 50 and 98 rH%.

This is controlled by re-heating the evaporator air with the defrost heaters.

Accuracy at rH set-point: 50% to 75%: +/-1.5%
75% to 95%: +/-3.0%