

# Contenedor frigorífico HC de 40 pies para -40°C

## DATOS TÉCNICOS

EL CAUDAL DE AIRE	NIVEL DE PRESIÓN DE SONIDO		
Tipo ISO 6346	45R1	Fugas de aire (Q) y térmica (U)	The air leakage is approximately 6 m <sup>3</sup> /hr. when the inside pressure of the container is 25.4 mm water column. The total heat loss of the container is approximately 48.3 watt/ °K (41.5 kcal/hr) at mean insulation wall temperature of 20°C.
Entorno de funcionamiento	The container is designed and manufactured for the carriage of chilled, fresh and frozen products at ambient temperature from +50°C to -30°C without effect on the strength of the structure. A Magnum Plus refrigeration unit of a "one piece picture frame type" will be fitted to the front end frame. The container is designed with a refrigeration unit to maintain the inside space temperature at +30°C to -40°C	Material de aislamiento	Cyclo Pentane blown rigid polyurethane foam; Flammability SE class (Self- extinguishing). In foamed sandwich panels where acrylic adhesive is coated on the inner surface of aluminum panels and stainless steel inner linings.
Normas y normativas	The containers comply with following authorized standards and regulations: ABS, Bureau Veritas, Lloyds Register, ISO/TC-104, ISO1496-2, ISO-668, TIR, CSC. The containers will be constructed to be capable of being handled without permanent deformation on following basis: Lifting, loaded or empty, at top corner fittings vertically by means of spreaders fitted with hooks, shackles or twist-locks. Lifting, loaded or empty, at bottom corner fittings using slings with terminal fittings at any angle between vertical and 45 degrees to the horizontal.		

## CARACTERÍSTICAS DIMENSIONES DE LA UNIDAD

Puerta de acceso	Double door CSS special using locking rods w/quick entry. Width 2,290 mm (90.15") * 2,569 mm (101.14"). Cargo access height: 2,560 mm (100.78").	Información general	Dimensions are rated at standard temperature of 20 °C (68 °F). Max. Gross Weight (R) kg / lbs 34,000 74,957 Tare Weight (T) kg / lbs 4,050 8,929 Payload (P) kg / lbs 29,950 66,028 External dimensions: Length 12,192 mm 480.0 inch Width 2,438 mm 96.0 inch Height 2,896 mm 114.0 inch Internal dimensions: Length 11,584 mm 456,1 inch Width 2,284 mm 89,9 inch Height 2,603 mm 102,5 inch
Puerta de escape	Escape door build into door. Possible to open from inside if man-trapped		
Suelo	The floor is composed of corrugated sub-floor and floor flat with reversed T-shaped floor-board with insulation of polyurethane The corrugated sub-floor is welded to the lower bottom side rails. Four (4) drain holes are provided at the front and rear end of the container. There is the float valve in the drain cover, which adjusts water in and out automatically. Floor Flat Reversed T-shaped extruded aluminum, flat surface is 30 mm high.		
Configuración	Internal light. Power on/off outside container Unit off button with timer relay Curtain tracks installed Man-trap alarm button. Audio using buzzer + Visual with red flashing lamp		
Opcional	Door ramp per customer		



# MARINE

| requirement