

## CSS SuperFreezer

### Extrem niedrige Temperaturen für kritische Fracht

- Extreme Kühlleistung
- Halten Sie extrem niedrige Temperaturen von bis zu  $-70\text{ }^{\circ}\text{C}$  aufrecht
- Schützen Sie die empfindlichsten und wertvollsten Frachten
- Lösung kann für den Straßen- oder Schiffstransport oder als Lager verwendet werden

| TECHNISCHE DATEN   |  |   |  |
|--|--|---|--|
| LUFTSTROM  | TECHNICAL SPECIFICATIONS   |   |  |
| Door access  | Ultra-Low temperature unit for installation in Reefer containers for stationary applications. All Aluminum "Picture frame". Cascade system with dual refrigeration circuit. R134a with Copeland 3 cylinder compressor. Charge 3.5 kg (7.7 lbs) R23 with Copeland Scroll compressor. Charge 3.2 kg (7.0 lbs)  | Setpoint Range<br><br>Ambient temperature Range<br><br>Required heat leakage of 20' box | 80db (A) in 250 Hz band. Measurement taken in front of the unit 1,5 m distance and 1,2 m above ground, with the unit operating at 50 Hz<br><br>ISO1496-2 CE ATP AHRI USDA TIR (International Customs Regulations for Containers)<br><br>630 kg (1,390 lbs) |
| Optional   | Pressure equalization valve (1400 Pascal / 140 mm WG) to avoid excessive vacuum in the container   |   |  |
| Required heat leakage of box   | $-70\text{ }^{\circ}\text{C}$ to $-10\text{ }^{\circ}\text{C}$ ( $-94\text{ }^{\circ}\text{F}$ to $-14\text{ }^{\circ}\text{F}$ )  |   |  |
| Container protection   | $-30\text{ }^{\circ}\text{C}$ to $+37.8\text{ }^{\circ}\text{C}$ ( $-22\text{ }^{\circ}\text{F}$ to $100\text{ }^{\circ}\text{F}$ )  |   |  |
| At setpoint $+21.1\text{ }^{\circ}\text{C}$ ( $70\text{ }^{\circ}\text{F}$ )                                   | 18 Watt/ $^{\circ}\text{K}$ @ 20C wall temperature, to ensure set-point at ambient   |   |  |
| Power supply   | 20 Watt/ $^{\circ}\text{K}$ @ 20C wall temperature, to ensure set-point at ambient   |   |  |
| DIMENSIONS AND WEIGHTS @ AMBIENT TEMPERATURE $+37.8\text{ }^{\circ}\text{C}$ ( $100\text{ }^{\circ}\text{F}$ ) |  | FEATURES  |  |
| At setpoint $-70\text{ }^{\circ}\text{C}$ ( $-94\text{ }^{\circ}\text{F}$ )                                    | 5,850 watt @ 460V/60Hz 5,086 watt @ 400V/50Hz  | Weight of SuperFreezer unit   | A/C 400 to 500 Volt 3 phase 60 Hz $\pm 2,5\%$ A/C 360 to 460 Volt 3 phase 50 Hz $\pm 2,5\%$  |
| Maximum power draw   | 3,880 watt @ 460V/60Hz 3,344 watt @ 400V/50Hz  | At setpoint $-30\text{ }^{\circ}\text{C}$ ( $-22\text{ }^{\circ}\text{F}$ )             | 32 Amp   |
| Weight of Magnum+ unit   | 8,250 watt @ 460V/60Hz 7,112 watt @ 400V/50Hz  | Capacity on Battery power $0\text{ }^{\circ}\text{C}$                                   | 18.3 m (60 LF) cable (3phase and ground) with CEE17 power plug (32 Amp; ground 3h)   |
|  |  | Capacity at 50 Hz $0\text{ }^{\circ}\text{C}$   | 19 kw during "pull down"   |
| COOLING CAPACITY   |  |   |  |
| Capacity at 50 Hz $-20\text{ }^{\circ}\text{C}$  | Advanced Microprocessor MP3000 Emerson Controls Temperature control using 6 NTC sensors Temperature accuracy: $\pm 1\text{ }^{\circ}\text{C}$ ( $\pm 1.8\text{ }^{\circ}\text{F}$ ) Datalogger document system parameters and changes, results of Pre-Trip Inspections, Alarms & messages, as well as temperature logs. Temperature logs are defaulted to 1 hour interval, and user can change to 30 min, 2 or 4 hr interval. Datalogger memory allow 15,000 temperature logs When power is disconnected, datalogger continue to log |   |  |

temperatures for 120 logs (3 days \* 24 hr interval). 3 USDA cargo sensor ports with Cannon receptacles (Option supply of 15m (49 LF) long cables with PT100 sensor (accuracy +/- 0.15°C (+/- 0.27°F)) Telematics (option) to allow two-way communication with controller. Using Global Network Satellite System and Global cellular LTE, 2G, 3G signal) Datalogger can be retrieved via serial port on unit, or via Telematics Controller continuously monitor health of system and components, an early indication can trigger a "message" and a critical issues trigger an "alarm" Unit controller has LED that flash red if an "Alarm" is active Defrost: To melt ice entering with cargo, and/or from door openings electrical defrost heaters are installed with capacity 8,160 watt @ 460/60Hz and 6,300 watt @ 400V/50Hz. Defrost activate every 6 hours, or per user lis controller set-up using temperature difference between evaporator coil sensor and return air sensor.