

## CSS SuperFreezer

### Сверхнизкие температуры для критически важных грузов

- Чрезвычайно высокая холодопроизводительность
- Поддерживайте сверхнизкие температуры до  $-70^{\circ}\text{C}$
- Защищите самые чувствительные и ценные грузы
- Решение можно использовать для транспортировки по суше или морю или в качестве хранилища

#### ТЕХНИЧЕСКИЕ ДАННЫЕ

РАСХОД ВОЗДУХА		ХАРАКТЕРИСТИКИ	
Тип установки	Ultra-Low temperature unit for installation in Reefer containers for stationary applications. All Aluminum "Picture frame". Cascade system with dual refrigeration circuit. R134a with Copeland 3 cylinder compressor. Charge 3.5 kg (7.7 lbs) R23 with Copeland Scroll compressor. Charge 3.2 kg (7.0 lbs)	Уровень шума	80db (A) in 250 Hz band. Measurement taken in front of the unit 1,5 m distance and 1,2 m above ground, with the unit operating at 50 Hz
Защита контейнеров	Pressure equalization valve (1400 Pascal / 140 mm WG) to avoid excessive vacuum in the container	Сертификация и стандарты проектирования	ISO1496-2 CE ATP AHRI USDA TIR (International Customs Regulations for Containers)
Диапазон заданных значений set point	$-70^{\circ}\text{C}$ to $-10^{\circ}\text{C}$ ( $-94^{\circ}\text{F}$ to $-14^{\circ}\text{F}$ )	Вес установки SuperFreezer	630 kg (1,390 lbs)
Диапазон температур окружающей среды	$-30^{\circ}\text{C}$ to $+37.8^{\circ}\text{C}$ ( $-22^{\circ}\text{F}$ to $100^{\circ}\text{F}$ )		
Требуемый теплоприток 10-футового кузова	18 Watt/°K @ 20C wall temperature, to ensure set-point at ambient		
Требуемый теплоприток 20-футового кузова	20 Watt/°K @ 20C wall temperature, to ensure set-point at ambient		

ХОЛОДОПРОИЗВОДИТЕЛЬНОСТЬ ПРИ ТЕМПЕРАТУРЕ ОКРУЖАЮЩЕЙ СРЕДЫ $+37,8^{\circ}\text{C}$		ЭЛЕКТРИЧЕСТВО	
При заданном значении set point $-60^{\circ}\text{C}$	5,850 watt @ 460V/60Hz 5,086 watt @ 400V/50Hz	Блок питания	A/C 400 to 500 Volt 3 phase 60 Hz $\pm 2,5\%$ A/C 360 to 460 Volt 3 phase 50 Hz $\pm 2,5\%$
При заданном значении set point $-70^{\circ}\text{C}$	3,880 watt @ 460V/60Hz 3,344 watt @ 400V/50Hz	Главный автоматический выключатель	32 Amp
При заданном значении set point $-30^{\circ}\text{C}$	8,250 watt @ 460V/60Hz 7,112 watt @ 400V/50Hz	Кабель питания	18.3 m (60 LF) cable (3phase and ground) with CEE17 power plug (32 Amp; ground 3h)
		Максимальная потребляемая мощность	19 kw during "pull down"

КОНТРОЛЛЕР	
Общие сведения	Advanced Microprocessor MP3000 Emerson Controls Temperature control using 6 NTC sensors Temperature accuracy: $\pm 1^{\circ}\text{C}$ ( $\pm 1.8^{\circ}\text{F}$ ) Datalogger document system parameters and changes, results of Pre-Trip Inspections,

Alarms & messages, as well as temperature logs. Temperature logs are defaulted to 1 hour interval, and user can change to 30 min, 2 or 4 hr interval. Datalogger memory allow 15,000 temperature logs When power is disconnected, datalogger continue to log temperatures for 120 logs (3 days \* 24 hr interval). 3 USDA cargo sensor ports with Cannon receptacles (Option supply of 15m (49 LF) long cables with PT100 sensor (accuracy +/- 0.15°C (+/- 0.27°F)) Telematics (option) to allow two-way communication with controller. Using Global Network Satellite System and Global cellular LTE, 2G, 3G signal) Datalogger can be retrieved via serial port on unit, or via Telematics Controller continuously monitor health of system and components, an early indication can trigger a "message" and a critical issues trigger an "alarm" Unit controller has LED that flash red if an "Alarm" is active

Defrost: To melt ice entering with cargo, and/or from door openings electrical defrost heaters are installed with capacity 8,160 watt @ 460/60Hz and 6,300 watt @ 400V/50Hz. Defrost activate every 6 hours, or per user's controller set-up using temperature difference between evaporator coil sensor and return air sensor.