

SLXi-200

Refrigeration Capacity	
Capacity on engine power 0°C	13500 W
Capacity on engine power -20°C	7500 W
Capacity on electrical stand by 0°C	10500 W
Capacity on electrical stand by -20°C	5900 W

Heating Capacity	
On the road	8000 W

Airflow	
Airflow volume @ 0 pa static pressure	5000 m ³ /hr
Airflow volume in fully loaded trailer	4680 m ³ /hr
Discharge velocity - airthrow	14 m/sec

Weight	
Model 30	737 (Whisper option + 85 kg) kg
Model 50	793 (Whisper option + 85 kg) kg

Engine	
Model	TK 486V
Rating	17.9 kW
Maintenance Interval	3000 hrs

Compressor	
Model	X430 C5
Displacement	492 cm ³

Electrical Stand by Motor	
Voltage / Phase / Frequency	400 / 3 / 50
Rating	9.3 kW

Refrigerant Charge	
Charge	5 kg

Generic (Boxlength, Refrigerant, ...)	
Boxlength	15 m
Refrigerant	R-452A
Controller	Smart Reefer 3

Pull down	
+20°C to -20°C (min)	160

Dimensions	Unit	Condenser
Height	2279 mm	2279 mm
Width	2076 mm	2076 mm
Depth	537.4 mm	537.4 mm

Caratteristiche e optional

Gestione del costo del ciclo di vita	
Fuel level sensor	<input type="checkbox"/> <input checked="" type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>

Acquisizione dati e comunicazioni	
TouchPrint Printer	<input checked="" type="checkbox"/>
ServiceWatch maintenance logger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
TrackKing? (tracking and load monitoring)	<input checked="" type="checkbox"/>
Wintrac? (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>

Protezione del carico	
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>
Air Chute	<input type="checkbox"/> <input checked="" type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
OptiSet Plus pre-set operating parameters	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/> <input checked="" type="checkbox"/>

Customization	
Solar Panel	<input type="checkbox"/> <input checked="" type="checkbox"/>
Snow Kit dealer fitted	<input type="checkbox"/> <input checked="" type="checkbox"/>
Tail lift battery charger	<input type="checkbox"/> <input checked="" type="checkbox"/>
Whisper kit acoustic	<input type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/> <input checked="" type="checkbox"/>
Protection bars (ships in multiples of 3)	<input checked="" type="checkbox"/>
Low voltage disconnect	<input checked="" type="checkbox"/>
Shock Protection Bars	<input checked="" type="checkbox"/>

Ease of Use	
Fuel filtration and priming system	<input type="checkbox"/> <input checked="" type="checkbox"/>
Kit Drop Down HMI	<input type="checkbox"/> <input checked="" type="checkbox"/>
Rear remote control SR-3	<input type="checkbox"/> <input checked="" type="checkbox"/>
Status light	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/> <input checked="" type="checkbox"/>

- Non disponibile
 Caratteristica di serie
 Optional: fornito dalla fabbrica
 Optional: fornito dal concessionario

SLXi-300

Refrigeration Capacity	
Capacity on engine power 0°C	15000 W
Capacity on engine power -20°C	7900 W
Capacity on electrical stand by 0°C	11900 W
Capacity on electrical stand by -20°C	6200 W

Heating Capacity	
On the road	12000 W

Airflow	
Airflow volume @ 0 pa static pressure	5000 m ³ /hr
Airflow volume in fully loaded trailer	4680 m ³ /hr
Discharge velocity - airthrow	14 m/sec

Weight	
Model 30	737 (Whisper option + 85 kg) kg
Model 50	793 (Whisper option + 85 kg) kg

Engine	
Model	TK 486V
Rating	17.9 kW
Maintenance Interval	3000 hrs

Compressor	
Model	X430 C5
Displacement	492 cm ³

Electrical Stand by Motor	
Voltage / Phase / Frequency	400 / 3 / 50
Rating	9.3 kW

Refrigerant Charge	
Charge	5 kg

Generic (Boxlength, Refrigerant, ...)	
Boxlength	15 m
Refrigerant	R-452A
Controller	Smart Reefer 3

Pull down	
+20°C to -20°C (min)	150

Dimensions	Unit	Condenser
Height	2279 mm	2279 mm
Width	2076 mm	2076 mm
Depth	537.4 mm	537.4 mm

Caratteristiche e optional

Life cost management	
Fuel level sensor	<input type="checkbox"/> <input checked="" type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>

Data capture & communications	
TouchPrint Printer	<input checked="" type="checkbox"/>
ServiceWatch maintenance logger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
TracKing? (tracking and load monitoring)	<input checked="" type="checkbox"/>
Wintrac? (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>

Load Protection	
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>
Air Chute	<input type="checkbox"/> <input checked="" type="checkbox"/>
Thermo King GDP PharmaSolutions Package	<input type="checkbox"/> <input checked="" type="checkbox"/>
OptiSet™ Plus	<input checked="" type="checkbox"/>
Produce Protection Plus (ETV & Temperature Modulation)	<input checked="" type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
OptiSet Plus pre-set operating parameters	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/> <input checked="" type="checkbox"/>

Customization	
Solar Panel	<input type="checkbox"/> <input checked="" type="checkbox"/>
Snow Kit dealer fitted	<input type="checkbox"/> <input checked="" type="checkbox"/>
Tail lift battery charger	<input type="checkbox"/> <input checked="" type="checkbox"/>
Whisper kit acoustic	<input type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/> <input checked="" type="checkbox"/>
Protection bars (ships in multiples of 3)	<input checked="" type="checkbox"/>
Low voltage disconnect	<input checked="" type="checkbox"/>
Shock Protection Bars	<input checked="" type="checkbox"/>

Ease of Use	
Fuel filtration and priming system	<input type="checkbox"/> <input checked="" type="checkbox"/>
Kit Drop Down HMI	<input type="checkbox"/> <input checked="" type="checkbox"/>
Rear remote control SR-3	<input type="checkbox"/> <input checked="" type="checkbox"/>
Status light	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/> <input checked="" type="checkbox"/>

- Non disponibile Caratteristica di serie
 Optional: fornito dalla fabbrica Optional: fornito dal concessionario

SLXi-400

Refrigeration Capacity	
Capacity on engine power 0°C	18700 W
Capacity on engine power -20°C	10000 W
Capacity on electrical stand by 0°C	13200 W
Capacity on electrical stand by -20°C	7100 W

Heating Capacity	
On the road	13300 W

Airflow	
Airflow volume @ 0 pa static pressure	5500 m ³ /hr
Airflow volume in fully loaded trailer	5100 m ³ /hr
Discharge velocity - airthrow	16 m/sec

Weight	
Model 30	737 (Whisper option + 85 kg) kg
Model 50	792 (Whisper option + 85 kg) kg

Engine	
Model	TK 486V
Rating	17.9 kW
Maintenance Interval	3000 hrs

Compressor	
Model	X430 C5
Displacement	492 cm ³

Electrical Stand by Motor	
Voltage / Phase / Frequency	400 / 3 / 50
Rating	9.3 kW

Refrigerant Charge	
Charge	5.5 kg

Generic (Boxlength, Refrigerant, ...)	
Boxlength	16 m
Refrigerant	R-452A
Controller	Smart Reefer 3

Pull down	
+20°C to -20°C (min)	120

Dimensions	Unit	Condenser
Height	2279 mm	2279 mm
Width	2076 mm	2076 mm
Depth	537.4 mm	537.4 mm

Caratteristiche e optional

Life cost management	
Fuel level sensor	<input type="checkbox"/> <input checked="" type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>

Data capture & communications	
TouchPrint Printer	<input checked="" type="checkbox"/>
ServiceWatch maintenance logger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
TrackKing? (tracking and load monitoring)	<input checked="" type="checkbox"/>
Wintrac? (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>

Load Protection	
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>
Air Chute	<input type="checkbox"/> <input checked="" type="checkbox"/>
Thermo King GDP PharmaSolutions Package	<input type="checkbox"/> <input checked="" type="checkbox"/>
Produce Protection Plus (ETV & Temperature Modulation)	<input checked="" type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
OptiSet Plus pre-set operating parameters	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/> <input checked="" type="checkbox"/>

Customization	
Solar Panel	<input type="checkbox"/> <input checked="" type="checkbox"/>
Snow Kit dealer fitted	<input type="checkbox"/> <input checked="" type="checkbox"/>
Tail lift battery charger	<input type="checkbox"/> <input checked="" type="checkbox"/>
Whisper kit acoustic	<input type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/> <input checked="" type="checkbox"/>
Protection bars (ships in multiples of 3)	<input checked="" type="checkbox"/>
Low voltage disconnect	<input checked="" type="checkbox"/>

Ease of Use	
Fuel filtration and priming system	<input type="checkbox"/> <input checked="" type="checkbox"/>
Kit Drop Down HMI	<input type="checkbox"/> <input checked="" type="checkbox"/>
Rear remote control SR-3	<input type="checkbox"/> <input checked="" type="checkbox"/>
Status light	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/> <input checked="" type="checkbox"/>

- Non disponibile
 Caratteristica di serie
 Optional: fornito dalla fabbrica
 Optional: fornito dal concessionario

SLXi SPECTRUM

Refrigeration Capacity	
Capacity on engine power 0°C	19100 W
Capacity on engine power -20°C	9000 W
Capacity on electrical stand by 0°C	11200 W
Capacity on electrical stand by -20°C	6100 W
Heating Capacity	
On the road	12000 W
Airflow	
Airflow volume @ 0 pa static pressure	5000 m ³ /hr
Airflow volume in fully loaded trailer	4680 m ³ /hr
Discharge velocity - airtrow	15 m/sec
Weight	
Model 30	759 (Whisper option + 85 kg) kg
Model 50	814 (Whisper option + 85 kg) kg
Engine	
Model	TK 486V
Rating	17.9 kW
Maintenance Interval	3000 hrs
Compressor	
Model	X430 C5
Displacement	492 cm ³
Electrical Stand by Motor	
Voltage / Phase / Frequency	400 / 3 / 50
Rating	9.3 kW
Refrigerant Charge	
Charge	9.5 kg
Generic (Boxlength, Refrigerant, ...)	
Boxlength	15 m
Refrigerant	R-452A
Controller	Smart Reefer 3

Dimensions	Unit	Condenser
Height	2279 mm	2279 mm
Width	2076 mm	2076 mm
Depth	537.4 mm	537.4 mm

Caratteristiche e optional

Life cost management	
Fuel level sensor	<input type="checkbox"/> <input checked="" type="checkbox"/>
Precision Temperature Control (PTC)	<input checked="" type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>

Data capture & communications	
TouchPrint Printer	<input checked="" type="checkbox"/>
ServiceWatch maintenance logger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
TrackKing? (tracking and load monitoring)	<input checked="" type="checkbox"/>
Wintrac? (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>

Load Protection	
Host Zone Null	<input checked="" type="checkbox"/>
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>
Air Chute	<input type="checkbox"/> <input checked="" type="checkbox"/>
Thermo King GDP PharmaSolutions Package	<input type="checkbox"/> <input checked="" type="checkbox"/>
Produce Protection Plus (ETV & Temperature Modulation)	<input checked="" type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/> <input checked="" type="checkbox"/>

Customization	
Solar Panel	<input type="checkbox"/> <input checked="" type="checkbox"/>
Snow Kit dealer fitted	<input type="checkbox"/> <input checked="" type="checkbox"/>
Tail lift battery charger	<input type="checkbox"/> <input checked="" type="checkbox"/>
Whisper kit acoustic	<input type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/> <input checked="" type="checkbox"/>
Protection bars (ships in multiples of 3)	<input checked="" type="checkbox"/>
Low voltage disconnect	<input checked="" type="checkbox"/>
Evaporator guard	<input type="checkbox"/> <input checked="" type="checkbox"/>

Ease of Use	
Fuel filtration and priming system	<input type="checkbox"/> <input checked="" type="checkbox"/>
Kit Drop Down HMI	<input type="checkbox"/> <input checked="" type="checkbox"/>
Rear remote control SR-3	<input type="checkbox"/> <input checked="" type="checkbox"/>
Status light	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/> <input checked="" type="checkbox"/>

- Non disponibile Caratteristica di serie
 Optional: fornito dalla fabbrica Optional: fornito dal concessionario

SLXi-300 Whisper Pro

Refrigeration Capacity	
Capacity on engine power 0°C	16500 W
Capacity on engine power -20°C	9400 W
Capacity on electrical stand by 0°C	10100 W
Capacity on electrical stand by -20°C	5800 W
Refrigeration Capacity High Speed	
Capacity on engine power 0°C	16500
Capacity on engine power -20°C	9400
Heating Capacity	
On the road	12000 W
Refrigeration Capacity PIEK Mode	
Capacity on engine power 0°C	10800
Capacity on engine power -20°C	6500
Airflow	
Airflow volume @ 0 pa static pressure	5000 m ³ /hr
Airflow volume in fully loaded trailer	4680 m ³ /hr
Discharge velocity - airthrow	14 m/sec
Weight	
Model 30	822 kg
Model 50	878 kg
Engine	
Model	TK 486V
Rating	17.9 kW
Maintenance Interval	3000 hrs
Compressor	
Model	X430 C5
Displacement	492 cm ³
Electrical Stand by Motor	
Voltage / Phase / Frequency	400 / 3 / 50
Rating	9.3 kW
Refrigerant Charge	
Charge	5 kg
Generic (Boxlength, Refrigerant, ...)	
Boxlength	15 m
Refrigerant	R-452A
Controller	Smart Reefer 3
Pull down	
+20°C to -20°C (min)	130

Dimensions	Unit	Condenser
Height	2279 mm	2279 mm
Width	2076 mm	2076 mm
Depth	537.4 mm	537.4 mm

Caratteristiche e optional

Life cost management	
Fuel level sensor	<input type="checkbox"/> <input checked="" type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>
Data capture & communications	
TouchPrint Printer	<input checked="" type="checkbox"/>
ServiceWatch maintenance logger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
TracKing? (tracking and load monitoring)	<input checked="" type="checkbox"/>
Wintrac? (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>
Load Protection	
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>
Air Chute	<input type="checkbox"/> <input checked="" type="checkbox"/>
Thermo King GDP PharmaSolutions Package	<input type="checkbox"/> <input checked="" type="checkbox"/>
OptiSet™ Plus	<input checked="" type="checkbox"/>
Produce Protection Plus (ETV & Temperature Modulation)	<input checked="" type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
OptiSet Plus pre-set operating parameters	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/> <input checked="" type="checkbox"/>
Customization	
Solar Panel	<input type="checkbox"/> <input checked="" type="checkbox"/>
Snow Kit dealer fitted	<input type="checkbox"/> <input checked="" type="checkbox"/>
Tail lift battery charger	<input type="checkbox"/> <input checked="" type="checkbox"/>
Whisper kit acoustic	<input type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/> <input checked="" type="checkbox"/>
Protection bars (ships in multiples of 3)	<input checked="" type="checkbox"/>
Low voltage disconnect	<input checked="" type="checkbox"/>
Ease of Use	
Fuel filtration and priming system	<input type="checkbox"/> <input checked="" type="checkbox"/>
Kit Drop Down HMI	<input type="checkbox"/> <input checked="" type="checkbox"/>
Rear remote control SR-3	<input type="checkbox"/> <input checked="" type="checkbox"/>
Status light	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/> <input checked="" type="checkbox"/>

Non disponibile Caratteristica di serie
 Optional: fornito dalla fabbrica Optional: fornito dal concessionario

SLXi SPECTRUM Whisper Pro

Refrigeration Capacity	
Capacity on engine power 0°C	18400 W
Capacity on engine power -20°C	9000 W
Capacity on electrical stand by 0°C	10500 W
Capacity on electrical stand by -20°C	6100 W
Refrigeration Capacity High Speed	
Capacity on engine power 0°C	18400
Capacity on engine power -20°C	9000
Heating Capacity	
On the road	12000 W
Refrigeration Capacity PIEK Mode	
Capacity on engine power 0°C	12400
Capacity on engine power -20°C	5800
Airflow	
Airflow volume @ 0 pa static pressure	5000 m ³ /hr
Airflow volume in fully loaded trailer	4680 m ³ /hr
Discharge velocity - airthrow	15 m/sec
Weight	
Model 30	844 kg
Model 50	900 kg
Engine	
Model	TK 486V
Rating	17.9 kW
Maintenance Interval	3000 hrs
Compressor	
Model	X430 C5
Displacement	492 cm ³
Electrical Stand by Motor	
Voltage / Phase / Frequency	400 / 3 / 50
Rating	9.3 kW
Refrigerant Charge	
Charge	9.5 kg
Generic (Boxlength, Refrigerant, ...)	
Boxlength	15 m
Refrigerant	R-452A
Controller	Smart Reefer 3

Dimensions	Unit	Condenser
Height	2279 mm	2279 mm
Width	2076 mm	2076 mm
Depth	537.4 mm	537.4 mm

Caratteristiche e optional

Life cost management	
Fuel level sensor	<input type="checkbox"/> <input checked="" type="checkbox"/>
Precision Temperature Control (PTC)	<input checked="" type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>
Data capture & communications	
TouchPrint Printer	<input checked="" type="checkbox"/>
ServiceWatch maintenance logger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
TrackIng? (tracking and load monitoring)	<input checked="" type="checkbox"/>
Wintrac? (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>
Load Protection	
Host Zone Null	<input checked="" type="checkbox"/>
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>
Air Chute	<input type="checkbox"/> <input checked="" type="checkbox"/>
Thermo King GDP PharmaSolutions Package	<input type="checkbox"/> <input checked="" type="checkbox"/>
Produce Protection Plus (ETV & Temperature Modulation)	<input checked="" type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/> <input checked="" type="checkbox"/>
Customization	
Solar Panel	<input type="checkbox"/> <input checked="" type="checkbox"/>
Snow Kit dealer fitted	<input type="checkbox"/> <input checked="" type="checkbox"/>
Tail lift battery charger	<input type="checkbox"/> <input checked="" type="checkbox"/>
Whisper kit acoustic	<input type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/> <input checked="" type="checkbox"/>
Protection bars (ships in multiples of 3)	<input checked="" type="checkbox"/>
Low voltage disconnect	<input checked="" type="checkbox"/>
Evaporator guard	<input type="checkbox"/> <input checked="" type="checkbox"/>
Ease of Use	
Fuel filtration and priming system	<input type="checkbox"/> <input checked="" type="checkbox"/>
Kit Drop Down HMI	<input type="checkbox"/> <input checked="" type="checkbox"/>
Rear remote control SR-3	<input type="checkbox"/> <input checked="" type="checkbox"/>
Status light	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/> <input checked="" type="checkbox"/>

- Non disponibile
 Caratteristica di serie
 Optional: fornito dalla fabbrica
 Optional: fornito dal concessionario