


A-360
Entry-level excellence

- Mechanically governed NRMM compliant engine
- 2-year Connectivity contract as Standard
- Flexible airflow
- Fully variable airflow independent of unit engine speed
- Reduced noise levels

Размеры	Установка
Height	2270 mm
Width	2076 mm
Depth	440 mm

Технические характеристики
Refrigeration Capacity
System net cooling capacity under A.T.P. conditions at 30 °C ambient

Capacity on engine power 0°C	15600 W
Capacity on engine power -20°C	8100 W
Capacity on electrical stand by 0°C	12700 W
Capacity on electrical stand by -20°C	6600 W

Heating Capacity: Box Temperature +2°C

Capacity on engine power (Outside air temperature: -20°C)	10750 W
---	---------

Airflow: independent from unit engine speed

Airflow volume @ 0 Pa static pressure - Default @ Pull Down	5000 m³/hr
Airflow volume @ 0 Pa static pressure - Max @ Pull Down	5500 m³/hr
Airflow volume @ 0 Pa static pressure - Default @ Set Point	3400 m³/hr
Airflow volume @ 0 Pa static pressure - Max @ Set Point	5000 m³/hr

Weight
including battery

Model Standard	830 kg
----------------	--------

Engine

Maintenance Interval	3000 hrs
Number of cylinders	4
Capacity	2,1 L

Electrical Stand by Motor

Voltage / Phase / Frequency	400/3/50
	460/3/60
Rating	9.3 kW

Sound Pressure Level

High Speed Diesel	65 dB(A)
Electric Standby	64 dB(A)

Функции и опции
Life cost management

Fuel consumption monitoring	<input type="radio"/>
Fuel level sensor	<input type="checkbox"/>
Fuel filtration and priming system	<input type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>

Data capture & communications

TracKing - 2 Years Contract	<input checked="" type="checkbox"/>
Trailer Assist EBS Harness	<input type="checkbox"/>
ServiceLog maintenance logger	<input checked="" type="checkbox"/>
ComplianceLog data logger	<input checked="" type="checkbox"/>
TouchLog independent data logger	<input type="checkbox"/>
Wintrac (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>

Load Protection

Adjustable airflow	<input checked="" type="checkbox"/>
Air Straightener (from Q4 2020)	<input type="checkbox"/>
Air Chute (from Q4 2020)	<input type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
OptiSet Plus pre-set operating parameters (from Q4 2020)	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/>
Diesel/electric auto switching	<input checked="" type="checkbox"/>

Customization

Whisper quiet operation	<input checked="" type="checkbox"/>
Solar Panel	<input type="checkbox"/>
Tail lift battery charger (from Q4 2020)	<input type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/>
Secured 3rd Party accessories power connection (from Q4 2020)	<input checked="" type="checkbox"/>

Ease of Use

Proactive alarm notifications	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/>

Не применимо Стандартная функция

Опция: поставляется с завода Опция: поставляется дилером


A-400
The new standard in trailer refrigeration

- Electronically governed NRMM compliant 3-speed engine
- Fuel consumption monitoring
- Enhanced 2-year Connectivity contract as standard
- Flexible airflow
- Fully variable airflow independent of unit engine speed
- Quietest "standard" unit in the market

Размеры	Установка
Height	2270 mm
Width	2076 mm
Depth	440 mm

Технические характеристики
Refrigeration Capacity
System net cooling capacity under A.T.P. conditions at 30 °C ambient

Capacity on engine power 0°C	16200 W
Capacity on engine power -20°C	8300 W
Capacity on electrical stand by 0°C	13000 W
Capacity on electrical stand by -20°C	6700 W

Heating Capacity: Box Temperature +2°C

Capacity on engine power (Outside air temperature: -20°C)	10750 W
---	---------

Airflow: independent from unit engine speed

Airflow volume @ 0 Pa static pressure - Default @ Pull Down	5000 m ³ /hr
Airflow volume @ 0 Pa static pressure - Max @ Pull Down	5500 m ³ /hr
Airflow volume @ 0 Pa static pressure - Default @ Set Point	3400 m ³ /hr
Airflow volume @ 0 Pa static pressure - Max @ Set Point	5000 m ³ /hr

Weight
including battery

Model Standard	830 kg
----------------	--------

Engine

Maintenance Interval	3000 hrs
Number of cylinders	4
Capacity	2,1 L

Electrical Stand by Motor

Voltage / Phase / Frequency	400/3/50
	460/3/60
Rating	9.3 kW

Sound Pressure Level

High Speed Diesel	65 dB(A)
Electric Standby	64 dB(A)

Функции и опции
Life cost management

Fuel consumption monitoring	<input checked="" type="checkbox"/>
Fuel level sensor	<input type="checkbox"/>
Fuel filtration and priming system	<input type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>

Data capture & communications

TrackIng - 2 Years Contract	<input checked="" type="checkbox"/>
Trailer Assist EBS Harness	<input type="checkbox"/>
ServiceLog maintenance logger	<input checked="" type="checkbox"/>
ComplianceLog data logger	<input checked="" type="checkbox"/>
TouchLog independent data logger	<input type="checkbox"/>
Wintrac (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>

Load Protection

Adjustable airflow	<input checked="" type="checkbox"/>
Air Straightener (from Q4 2020)	<input type="checkbox"/>
Air Chute (from Q4 2020)	<input type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
OptiSet Plus pre-set operating parameters (from Q4 2020)	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/>
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>

Customization

Chrome grille	<input type="checkbox"/>
Whisper quiet operation	<input checked="" type="checkbox"/>
Solar Panel	<input type="checkbox"/>
Tail lift battery charger (from Q4 2020)	<input type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/>
Secured 3rd Party accessories power connection (from Q4 2020)	<input checked="" type="checkbox"/>

Ease of Use

Proactive alarm notifications	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/>

Не применимо Стандартная функция

Опция: поставляется с завода Опция: поставляется дилером



A-500

When your cargo deserves the best of the best

- Electronically governed NRMM compliant 4-speed engine
- Fuel consumption monitoring
- Most accurate temperature control in the market
- Fastest pulldown
- Fully variable airflow independent of unit engine speed
- Quietest high-capacity unit in the Market

Технические характеристики

Refrigeration Capacity

System net cooling capacity under A.T.P. conditions at 30 °C ambient

Capacity on engine power 0°C	19500 W
Capacity on engine power -20°C	10400 W
Capacity on electrical stand by 0°C	14600 W
Capacity on electrical stand by -20°C	8400 W

Heating Capacity: Box Temperature +2°C

Capacity on engine power (Outside air temperature: -20°C)	15900 W
---	---------

Airflow: independent from unit engine speed

Airflow volume @ 0 Pa static pressure - Default @ Pull Down	5500 m ³ /hr
Airflow volume @ 0 Pa static pressure - Max @ Pull Down	6000 m ³ /hr
Airflow volume @ 0 Pa static pressure - Default @ Set Point	3400 m ³ /hr
Airflow volume @ 0 Pa static pressure - Max @ Set Point	5500 m ³ /hr

Weight

including battery

Model Standard	835 kg
----------------	--------

Engine

Maintenance Interval	3000 hrs
Number of cylinders	4
Displacement	2,1

Electrical Stand by Motor

Voltage / Phase / Frequency	400/3/50 460/3/60
Rating	9.3 kW

Sound Pressure Level

High Speed Diesel	67 dB(A)
Electric Standby	64 dB(A)

Размеры	Установка
Height	2270 mm
Width	2076 mm
Depth	440 mm

Функции и опции

Life cost management

Fuel consumption monitoring	<input checked="" type="checkbox"/>
Fuel level sensor	<input type="checkbox"/>
Fuel filtration and priming system	<input type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>

Data capture & communications

TrackIng - 2 Years Contract	<input checked="" type="checkbox"/>
Trailer Assist EBS Harness	<input type="checkbox"/>
ServiceLog maintenance logger	<input checked="" type="checkbox"/>
ComplianceLog data logger	<input checked="" type="checkbox"/>
TouchLog independent data logger	<input type="checkbox"/>
Wintrac (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>

Load Protection

Adjustable airflow	<input checked="" type="checkbox"/>
Air Straightener (from Q4 2020)	<input type="checkbox"/>
Air Chute (from Q4 2020)	<input type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
OptiSet Plus pre-set operating parameters (from Q4 2020)	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/>
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>

Customization

Whisper quiet operation	<input checked="" type="checkbox"/>
Solar Panel	<input type="checkbox"/>
Tail lift battery charger (from Q4 2020)	<input type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/>
Secured 3rd Party accessories power connection (from Q4 2020)	<input checked="" type="checkbox"/>

Ease of Use

Proactive alarm notifications	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/>

Не применимо

Стандартная функция

Опция: поставляется с завода

Опция: поставляется дилером