



C-350e

Dimensions	Unit	Condenser
Height	227 mm	227 mm
Width	789 mm	789 mm
Depth	500 mm	500 mm

□□□□□□□□ □ □□□□□

????????????? ?????? ?????????? ? ???????? ?????? ???????	
ThermoKare Service contracts	<input checked="" type="checkbox"/>

???? ? ?????????? ???????	
USB Datalogger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
Datalogger Jr	<input checked="" type="checkbox"/>

?????? ??????	
Bumper feet roof mounting	<input type="checkbox"/>
HMI holder	<input type="checkbox"/>
Kit hoses large (upgrade)	<input type="checkbox"/>
Kit swivel manifold (upgrade)	<input type="checkbox"/>
Hose Cover	<input type="checkbox"/>
Muffler kit	<input type="checkbox"/>
Snow Cover (kit deflector Small)	<input type="checkbox"/>

○ □ □□□□□□□□

● □□□□□□□□□□ □□□□□□□□

□ □□□□□□□ □ □□□□□ □ □□□□□□

■ □□□□□□ □□□□□□□□ □□□□□□□□

Refrigeration Capacity	
Capacity on engine power 0°C	2965 W

Weight	
Condenser	23 kg
Slimline Evaporator	18 kg
Swash Plate Compressor	6.8 kg

Compressor	
Model	QP15
Displacement	146.7 cm ³
Number of cylinders	6

Refrigerant Charge	
Charge	1.2 kg

Generic (Boxlength, Refrigerant, ...)	
Box volume	25 m ³
Refrigerant	R-134a
Airflow	1400 m ³ /hr
Controller	CSR

Defrost	
Defrost	Automatic hot gas defrost

C-450e

Refrigeration Capacity	
Capacity on engine power 0°C	3315 W

Weight	
Condenser	31 kg
Slimline Evaporator	18 kg
Swash Plate Compressor	7.1 kg

Compressor	
Model	QP16
Displacement	163 cm ³
Number of cylinders	6

Refrigerant Charge	
Charge	1.2 kg

Generic (Boxlength, Refrigerant, ...)	
Box volume	31 m ³
Refrigerant	R-134a
Airflow	1650 m ³ /hr
Controller	CSR

Defrost	
Defrost	Automatic hot gas defrost

Dimensions	Unit	Condenser
Height	213 mm	213 mm
Width	1180 mm	1180 mm
Depth	485 mm	485 mm

Optional Equipment

Optional Equipment	
ThermoKare Service contracts	<input type="checkbox"/>

Optional Equipment	
TouchPrint data logger	<input type="checkbox"/>
USB data port	<input type="checkbox"/>
Datalogger Jr	<input type="checkbox"/>

Optional Equipment	
Bumper feet roof mounting	<input type="checkbox"/>
HMI holder	<input type="checkbox"/>
Kit hoses large (upgrade)	<input type="checkbox"/>
Kit swivel manifold (upgrade)	<input type="checkbox"/>
Hose Cover	<input type="checkbox"/>
Muffler kit	<input type="checkbox"/>
Snow Cover (kit deflector Big)	<input type="checkbox"/>
Harness Extension 2m/4m/6m	<input type="checkbox"/>

Optional Equipment: (Empty)

Optional Equipment: (Selected)

Optional Equipment: (Empty)

Optional Equipment: (Selected)

C-350e MAX

Dimensions	Unit	Condenser
Height	227 mm	227 mm
Width	789 mm	789 mm
Depth	500 mm	500 mm

□□□□□□ □ □□□□□

Refrigeration Capacity	
Capacity on engine power 0°C	3330 W
Capacity on engine power -20°C	1840 W

Heating Capacity	
On the road	3100 W

Weight	
Condenser	23 kg
Slimline Evaporator	18 kg
Swash Plate Compressor	6.8 kg

Compressor	
Model	QP15
Displacement	146.7 cm ³
Number of cylinders	6

Refrigerant Charge	
Charge	1.2 kg

Generic (Boxlength, Refrigerant, ...)	
Box volume	17 - 28 m ³
Refrigerant	R-404A/R-452A
Airflow	1400 m ³ /hr
Controller	CSR

Defrost	
Defrost	Automatic hot gas defrost

????????? ?????? ?????????? ? ???????? ????? ??????		
ThermoKare Service contracts		<input checked="" type="checkbox"/>

???? ? ???????? ??????		
USB Datalogger		<input checked="" type="checkbox"/>
TouchPrint data logger		<input checked="" type="checkbox"/>
Datalogger Jr		<input checked="" type="checkbox"/>

?????? ??????		
Bumper feet roof mounting		<input type="checkbox"/>
HMI holder		<input type="checkbox"/>
Kit hoses large (upgrade)		<input type="checkbox"/>
Kit swivel manifold (upgrade)		<input type="checkbox"/>
Hose Cover		<input type="checkbox"/>
Muffler kit		<input type="checkbox"/>
Snow Cover (kit deflector Big)		<input type="checkbox"/>

- | | |
|---|--|
| <input type="radio"/> □□ □□□□□□□□
<input type="checkbox"/> □□□□□: □□□□□□□□□□ □ □□□□□ | <input checked="" type="radio"/> □□□□□□□□□□ □□□□□□□□
<input checked="" type="checkbox"/> □□□□□□□□□□□□ □ □□□□□□□ |
|---|--|

V-100

Dimensions	Unit	Condenser
Height	242 mm	242 mm
Width	789 mm	789 mm
Depth	500 mm	500 mm

○○○○○○○ ○ ○○○○○

?????????? ?????? ?????????? ? ??????? ????? ??????	
ThermoKare Service contracts	<input checked="" type="checkbox"/>

???? ? ????????? ??????	
USB Datalogger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
Wintrac? (data analysis software)	<input checked="" type="checkbox"/>
Datalogger Jr	<input checked="" type="checkbox"/>

?????? ??????	
Bumper feet roof mounting	<input checked="" type="checkbox"/>
HMI holder	<input checked="" type="checkbox"/>
Kit hoses large (upgrade)	<input checked="" type="checkbox"/>
Kit swivel manifold (upgrade)	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/>
Din Adapter	<input type="checkbox"/>
Hose Cover	<input type="checkbox"/>
Muffler kit	<input type="checkbox"/>
Snow Cover (kit deflector Small)	<input type="checkbox"/>

○ ○○○○○○○○ ○○○○○○○○○○ ○○○○○○○○
 ○○○○○: ○○○○○○○○○○○○ ○ ○○○○○○ ○○○○○: ○○○○○○○○○○○○ ○○○○○○○○

Refrigeration Capacity	
Capacity on engine power 0°C	1665 W
Capacity on engine power -20°C	680 W
Capacity on electrical stand by 0°C	975 W
Capacity on electrical stand by -20°C	390 W

Weight	
Slimline Evaporator	9 kg
Installation kit	24 kg
Condenser w/o electric stand-by	25 kg
Condenser with electric stand-by	43 kg
Swash Plate Compressor	6.5 kg

Compressor	
Model	QP08N
Displacement	131 cm ³
Number of cylinders	6

Electrical Stand by Motor	
Voltage / Phase / Frequency	230/1/50
Rating	1.6 kW

Refrigerant Charge	
Charge	V-100 10: 0.62 -- V-100 20: 1.0 kg

Generic (Boxlength, Refrigerant, ...)	
Box volume	5 - 12 m ³
Refrigerant	R-134a
Airflow	745 m ³ /hr
Controller	DSR III

Defrost	
Defrost	Automatic hot gas defrost

V-100 MAX

Dimensions	Unit	Condenser
Height	242 mm	242 mm
Width	789 mm	789 mm
Depth	500 mm	500 mm

□□□□□□ □ □□□□□

?????????? ?????? ?????????? ? ????????? ?????? ???????	
ThermoKare Service contracts	<input type="checkbox"/>

???? ? ?????????? ???????	
USB Datalogger	<input type="checkbox"/>
TouchPrint data logger	<input type="checkbox"/>
Wintrac? (data analysis software)	<input type="checkbox"/>
Datalogger Jr	<input type="checkbox"/>

?????? ??????	
Bumper feet roof mounting	<input checked="" type="checkbox"/>
HMI holder	<input checked="" type="checkbox"/>
Kit hoses large (upgrade)	<input checked="" type="checkbox"/>
Kit swivel manifold (upgrade)	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/>
Din Adapter	<input type="checkbox"/>
Hose Cover	<input type="checkbox"/>
Muffler kit	<input type="checkbox"/>
Snow Cover (kit deflector Small)	<input type="checkbox"/>

 □ □□□□□□□□□

 □□□□□□□□□□ □□□□□□□□

 □□□□□: □□□□□□□□□□□ □ □□□□□□□

 □□□□□: □□□□□□□□□□□ □□□□□□□□

Refrigeration Capacity	
Capacity on engine power 0°C	2080 W
Capacity on engine power -20°C	1090 W
Capacity on electrical stand by 0°C	1260 W
Capacity on electrical stand by -20°C	695 W

Heating Capacity	
On the road	1900 W
Electric Stand By Operation	1100 W

Weight	
Installation kit	24 kg
Condenser w/o electric stand-by	25 kg
Condenser with electric stand-by	43 kg
Evaporator	9 kg
Swash Plate Compressor	6.5 kg

Compressor	
Model	QP08N
Displacement	131 cm ³
Number of cylinders	6

Electrical Stand by Motor	
Voltage / Phase / Frequency	230/1/50
Rating	1.6 kW

Refrigerant Charge	
Charge	10/30: 0.62 -- 20: 1 -- 50: 1.2 kg

Generic (Boxlength, Refrigerant, ...)	
Box volume	8 - 16 m ³
Refrigerant	R-404A/R-452A
Airflow	745 m ³ /hr
Controller	DSR III

Defrost	
Defrost	Automatic hot gas defrost

V-200s MAX

Refrigeration Capacity	
Capacity on engine power 0°C	2410 W
Capacity on engine power -20°C	1180 W
Capacity on electrical stand by 0°C	1500 W
Capacity on electrical stand by -20°C	650 W

Heating Capacity	
On the road	2200 W
Electric Stand By Operation	1300 W

Weight	
Condenser w/o electric stand-by	25 kg
Condenser with electric stand-by	43 kg
Evaporator	14 kg

Engine	
Rating	1.6 kW
no. of cylinders/displacement	6/82 cm ³

Compressor	
Model	QP08N
Displacement	131 cm ³

Refrigerant Charge	
Charge	1.1 kg

Generic (Boxlength, Refrigerant, ...)	
Box volume	10 - 19 m ³
Refrigerant	R-404A/R-452A
Airflow	1000 m ³ /hr
Controller	DSR III

Dimensions	Unit	Condenser
Height	242 mm	242 mm
Width	789 mm	789 mm
Depth	500 mm	500 mm

☐ ☐

????????? ?????? ?????????? ? ??????? ????? ??????	
ThermoKare Service contracts	<input checked="" type="checkbox"/>

???? ? ?????????? ??????	
USB Datalogger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
Wintrac? (data analysis software)	<input checked="" type="checkbox"/>
Datalogger Jr	<input checked="" type="checkbox"/>

?????? ??????	
Hose extension 2 m/4 m/6 m	<input type="checkbox"/>
Bumper feet roof mounting	<input checked="" type="checkbox"/>
HMI holder	<input checked="" type="checkbox"/>
Kit hoses large (upgrade)	<input checked="" type="checkbox"/>
Kit swivel manifold (upgrade)	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/>
Din Adapter	<input type="checkbox"/>
Hose Cover	<input type="checkbox"/>
Muffler kit	<input type="checkbox"/>
Snow Cover (kit deflector Small)	<input type="checkbox"/>

- ☐

☐ ☐

☐ ☐

☐ ☐

V-200 MAX

Dimensions	Unit	Condenser
Height	221 mm	
Width	1180 mm	
Depth	485 mm	

□□□□□□□□ □ □□□□□

□□□□□□□□□□ □□□□□□□□□□ □ □□□□□□□ □□□□□ □□□□□□□		
ThermoKare Service contracts		<input checked="" type="checkbox"/>

□□□□□ □ □□□□□□□□ □□□□□□		
USB Datalogger		<input checked="" type="checkbox"/>
TouchPrint data logger		<input checked="" type="checkbox"/>
Wintrac? (data analysis software)		<input checked="" type="checkbox"/>
Datalogger Jr		<input checked="" type="checkbox"/>

□□□□□□ □□□□□		
Bumper feet roof mounting		<input checked="" type="checkbox"/>
HMI holder		<input checked="" type="checkbox"/>
Kit hoses large (upgrade)		<input checked="" type="checkbox"/>
Kit swivel manifold (upgrade)		<input checked="" type="checkbox"/>
Door switches		<input type="checkbox"/>
Din Adapter		<input type="checkbox"/>
Hose Cover		<input type="checkbox"/>
Muffler kit		<input type="checkbox"/>
Snow Cover (kit deflector Small)		<input type="checkbox"/>
Snow Cover (kit deflector Big)		<input type="checkbox"/>
Harness Extension 2m/4m/6m		<input type="checkbox"/>

○ □□ □□□□□□□□ □□□□□□□□□□ □□□□□□ □□□□□□ □□□□□□ □□□□□□ □□□□□□ □□□□□□ □□□□□□ □□□□□□

Refrigeration Capacity	
Capacity on engine power 0°C	2770 W
Capacity on engine power -20°C	1460 W
Capacity on electrical stand by 0°C	1970 W
Capacity on electrical stand by -20°C	1130 W
Heating Capacity	
On the road	2800 W
Electric Stand By Operation	2050 W
Weight	
Model 30	25 kg
Model 50	75 kg
Installation kit	24 kg
Evaporator	15 kg
Swash Plate Compressor	6.9 kg
Compressor	
Model	QP13
Displacement	131 cm ³
Number of cylinders	6
Electrical Stand by Motor	
Voltage / Phase / Frequency	230/1/50 -- 230/1/60 -- 400/3/50 -- 230/3/50 -- 230/3/60
Rating	3.7 kW
Refrigerant Charge	
Charge	10/30: 1.0 -- 20/50: 1.2 kg
Generic (Boxlength, Refrigerant, ...)	
Box volume	13 - 22 m ³
Refrigerant	R-404A/R-452A
Airflow	1100 m ³ /hr
Controller	DSR III
Defrost	
Defrost	Automatic hot gas defrost

V-500

Refrigeration Capacity	
Capacity on engine power 0°C	3915 W
Capacity on engine power -20°C	1655 W
Capacity on electrical stand by 0°C	3160 W
Capacity on electrical stand by -20°C	1090 W

Weight	
Condenser w/o electric stand-by	53 kg
Condenser with electric stand-by	125 kg
Evaporator	25.5 kg
Swash Plate Compressor	7.1 kg

Compressor	
Model	QP16
Displacement	163 cm ³
Number of cylinders	6

Electrical Stand by Motor	
Voltage / Phase / Frequency	400/3/50 -- 380/3/60 -- 230/3/50 -- 230/3/60 -- 230/1/50 --230/1/60
Rating	6.4 kW

Refrigerant Charge	
Charge	10: 2.0 -- 20: 2.2 kg

Generic (Boxlength, Refrigerant, ...)	
Box volume	13 - 30 m ³
Refrigerant	R-134a
Airflow	2200 m ³ /hr
Controller	DSR III

Defrost	
Defrost	Automatic hot gas defrost

Dimensions	Unit	Condenser
Height	448 mm	448 mm
Width	1339 mm	1339 mm
Depth	475 mm	475 mm

00000000 0 000000

0000000000 000000 0000000000 0 00000000 000000 0000000	
ThermoKare Service contracts	<input type="checkbox"/>

0000 0 000000000 0000000	
USB Datalogger	<input type="checkbox"/>
TouchPrint data logger	<input type="checkbox"/>
Wintrac? (data analysis software)	<input type="checkbox"/>
Datalogger Jr	<input type="checkbox"/>

000000 000000	
Bumper feet roof mounting	<input checked="" type="checkbox"/>
HMI holder	<input checked="" type="checkbox"/>
Kit hoses large (upgrade)	<input checked="" type="checkbox"/>
Kit swivel manifold (upgrade)	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/>
Din Adapter	<input type="checkbox"/>
Hose Cover	<input type="checkbox"/>

- 00 0000000000
- 000000: 000000000000000 0 0000000
- 0000000000000000 00000000
- 0000000: 000000000000000 00000000

V-800

Refrigeration Capacity	
Capacity on engine power 0°C	5175 W
Capacity on electrical stand by 0°C	4920 W

Weight	
Condenser w/o electric stand-by	100 kg
Condenser with electric stand-by	160 kg
Evaporator	35 kg
Swash Plate Compressor	8.5 kg

Compressor	
Model	QP21
Displacement	215 cm ³
Number of cylinders	10

Electrical Stand by Motor	
Voltage / Phase / Frequency	400/3/50 -- 400/3/60 -- 230/3/50 -- 230/3/60
Rating	8.2 kW

Refrigerant Charge	
Charge	10: 4.55 -- 20: 4.85 kg

Generic (Boxlength, Refrigerant, ...)	
Box volume	44 m ³
Refrigerant	R-134a
Airflow	2680 m ³ /hr
Controller	DSR III

Defrost	
Defrost	Automatic hot gas defrost

Dimensions	Unit	Condenser
Height	458 mm	458.7 mm
Width	1592 mm	1592 mm
Depth	523 mm	523 mm

□ □ □ □ □ □ □ □ □ □ □ □

????????? ?????? ?????????? ? ????????? ?????? ??????	
ThermoKare Service contracts	<input type="checkbox"/>

???? ? ?????????? ??????	
USB Datalogger	<input type="checkbox"/>
TouchPrint data logger	<input type="checkbox"/>
Wintrac? (data analysis software)	<input type="checkbox"/>
Datalogger Jr	<input type="checkbox"/>

?????? ??????	
Bumper feet roof mounting	<input checked="" type="checkbox"/>
HMI holder	<input checked="" type="checkbox"/>
Kit hoses large (upgrade)	<input checked="" type="checkbox"/>
Kit swivel manifold (upgrade)	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/>
Din Adapter	<input type="checkbox"/>
Hose Cover	<input type="checkbox"/>

□ □ □ □ □ □ □ □ □ □ □ □
 □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □
 □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

V-800 MAX

Refrigeration Capacity	
Capacity on engine power 0°C	7790 W
Capacity on engine power -20°C	4160 W
Capacity on electrical stand by 0°C	7030 W
Capacity on electrical stand by -20°C	3795 W
Heating Capacity	
On the road	7030 W
Electric Stand By Operation	6450 W
Weight	
Condenser w/o electric stand-by	100 kg
Condenser with electric stand-by	160 kg
Evaporator	35 kg
Swash Plate Compressor	8.5 kg
Compressor	
Model	QP21
Displacement	215 cm ³
Number of cylinders	10
Electrical Stand by Motor	
Voltage / Phase / Frequency	400/3/50 -- 400/3/60 -- 230/3/50 -- 230/3/60
Rating	8.2 kW
Refrigerant Charge	
Charge	10/30: 4.7 -- 20/50: 5 kg
Generic (Boxlength, Refrigerant, ...)	
Box volume	42 - 54 m ³
Refrigerant	R-404A/R-452A
Airflow	2680 m ³ /hr
Controller	DSR III
Defrost	
Defrost	Automatic hot gas defrost

Dimensions	Unit	Condenser
Height	458.7 mm	458.7 mm
Width	1592 mm	1592 mm
Depth	523 mm	523 mm

- □ □□□□□
- ThermoKare Service contracts
 - USB Datalogger
 - TouchPrint data logger
 - Wintrac? (data analysis software)
 - Datalogger Jr
 - Bumper feet roof mounting
 - HMI holder
 - Kit hoses large (upgrade)
 - Kit swivel manifold (upgrade)
 - Door switches
 - Din Adapter
 - Hose Cover
- □□ □□□□□□ □□ □□□□□□ □□□□□□ □□□□□□
- □□□□: □□□□□□□□□□ □ □□□□□
- □□□□□□□□ □□□□□□
- □□□□□: □□□□□□□□ □□□□□□

V-200 MAX Spectrum

Refrigeration Capacity	
Capacity on engine power ES100 MAX+ES100 MAX -20°C	1750 W
Capacity on electrical stand by -20°C	1170 W

Heating Capacity	
On the road	2800 W
Electric Stand By Operation	2050 W

Weight	
Condenser w/o electric stand-by	25 kg
Condenser with electric stand-by	75 kg
Swash Plate Compressor	6.9 kg
Evaporator ES100 MAX	9 kg

Compressor	
Model	QP13
Displacement	131 cm ³
Number of cylinders	6

Electrical Stand by Motor	
Voltage / Phase / Frequency	230/1/50 -- 230/1/60 -- 400/3/50 -- 230/3/50 -- 230/3/60
Rating	3.8 kW

Refrigerant Charge	
Charge	1.35 kg

Generic (Boxlength, Refrigerant, ...)	
Box volume	12 m ³
Refrigerant	R-404A/R-452A
Airflow	695 m ³ /hr
Controller	DSR III

Defrost	
Defrost	Automatic hot gas defrost

Dimensions	Unit	Condenser
Height	221 mm	
Width	1180 mm	
Depth	535 mm	

□□□□□□□ □ □□□□□

???????????? ???? ???? ???? ???? ???? ???? ???? ???? ???? ???? ???? ?	
ThermoKare Service contracts	<input checked="" type="checkbox"/>

???? ? ???? ???? ???? ?	
USB Datalogger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
Wintrac? (data analysis software)	<input checked="" type="checkbox"/>
Datalogger Jr	<input checked="" type="checkbox"/>

????? ???? ?	
Bumper feet roof mounting	<input checked="" type="checkbox"/>
HMI holder	<input checked="" type="checkbox"/>
Kit swivel manifold (upgrade)	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/>
Din Adapter	<input type="checkbox"/>
Hose Cover	<input type="checkbox"/>
Muffler kit	<input type="checkbox"/>
Snow Cover (kit deflector Small)	<input type="checkbox"/>
Snow Cover (kit deflector Big)	<input type="checkbox"/>
Harness Extension 2m/4m/6m	<input type="checkbox"/>

○ □ □□□□□□□ □□□□□□□ □□□□□□□ □□□□□□□□□□ □□□□□□ □□□□□□□□ □□□□□□□□ □□□□□□□□□□

● □□□□□□□□ □□□□□□ □□□□□□ □□□□□□ □□□□□□□□ □□□□□□□□ □□□□□□□□ □□□□□□□□□□

V-500 MAX SPECTRUM

Dimensions	Unit	Condenser
Height	448 mm	448 mm
Width	475 mm	1339 mm
Depth	1339 mm	475 mm

○○○○○○○ ○○○○○○

?????????? ?????? ?????????? ? ??????? ?????? ???????

 ThermoKare Service contracts

???? ? ?????????? ???????

 USB Datalogger

 TouchPrint data logger

 Wintrac? (data analysis software)

 Datalogger Jr

?????? ??????

 Bumper feet roof mounting

 HMI holder

 Kit swivel manifold (upgrade)

 Door switches

 Din Adapter

 Hose Cover

 Harness Extension 2m/4m/6m
 ○○○○○○○○○○

 ○○○○○○○○○○ ○○○○○○

 ○○○○○: ○○○○○○○○○○ ○○○○○○

 ○○○○○: ○○○○○○○○○○ ○○○○○○

Refrigeration Capacity	
Capacity on engine power -20°C	2390 W
Capacity on engine power ES300 MAX+ES300 MAX -20°C	2390 W
Capacity on engine power ES300 MAX+ES150 MAX -20°C	2390 W
Capacity on engine power ES300 MAX+2xES150 MAX -20°C	2390 W
Capacity on engine power ES150 MAX+ES150 MAX -20°C	2390 (2 x ES150 + 2 x ES150) W
Capacity on electrical stand by -20°C	2005 W
Capacity on electrical stand by ES300 MAX+ES300 MAX -20°C	2005 W
Capacity on electrical stand by ES300 MAX+ES150 MAX -20°C	2005 W
Capacity on electrical stand by ES300 MAX+2xES150 MAX -20°C	2005 W
Capacity on electrical stand by ES150 MAX+ES150 MAX -20°C	2005 (2 x ES150 + 2 x ES150) W

Refrigeration Capacity: Individual Cooling Capacity	
Capacity on engine power ES150 MAX 0°C	2925 W
Capacity on engine power ES150 MAX -20°C	1580 W
Capacity on engine power 2 X ES150 MAX 0°C	3975 W
Capacity on engine power 2 X ES150 MAX -20°C	2055 W
Capacity on engine power ES300 MAX 0°C	3585 W
Capacity on engine power ES300 MAX -20°C	1930 W
Capacity on electrical stand by ES150 MAX 0°C	2580 W
Capacity on electrical stand by ES150 MAX -20°C	1380 W
Capacity on electrical stand by 2 X ES150 MAX 0°C	3595 W
Capacity on electrical stand by 2 X ES150 MAX -20°C	1770 W
Capacity on electrical stand by ES300 MAX 0°C	3385 W
Capacity on electrical stand by ES300 MAX -20°C	1745 W

Heating Capacity	
On the road	3600 W
Electric Stand By Operation	3120 W

Airflow	
2XES150+2XES150	(2x700)+(2x700) m ³ /hr
ES300+2XES150	1185+(2x700) m ³ /hr
ES300+ES150	1185+700 m ³ /hr
ES300+ES300	2x1185 m ³ /hr

Weight	
Condenser w/o electric stand-by	53 kg
Condenser with electric stand-by	125 kg
Evaporator ES300 MAX	18 kg
Evaporator ES150 MAX	12.5 kg
Swash Plate Compressor	7.1 kg

Compressor	
Model	QP16
Displacement	163 cm ³
Number of cylinders	6

Electrical Stand by Motor	
Voltage / Phase / Frequency	400/3/50 --230/3/50 -- 230/3/60 -- 230/1/50 -- 230/1/60
Rating	6.4 kW

Refrigerant Charge	
Charge	10: 2.3 -- 20/30: 2.4 -- 50: 2.5 kg

Generic (Boxlength, Refrigerant, ...)	
Box volume	22 m ³
Refrigerant	R-404A/R-452A
Airflow	1185 m ³ /hr
Controller	DSR III

Defrost	
Defrost	Automatic hot gas defrost

V-800 MAX Spectrum

Dimensions	Unit	Condenser
Height	458.7 mm	458.7 mm
Width	1592 mm	1592 mm
Depth	523 mm	523 mm

0000000 0 00000

?????????? ?????? ??????????? ? ??????? ????? ???????	
ThermoKare Service contracts	<input checked="" type="checkbox"/>
???? ? ????????????? ???????	
USB Datalogger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
Wintrac? (data analysis software)	<input checked="" type="checkbox"/>
Datalogger Jr	<input checked="" type="checkbox"/>

?????? ??????	
Bumper feet roof mounting	<input checked="" type="checkbox"/>
HMI holder	<input checked="" type="checkbox"/>
Kit swivel manifold (upgrade)	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/>
Din Adapter	<input type="checkbox"/>
Hose Cover	<input type="checkbox"/>

00 0000000000

000000: 000000000000000 0 0000000

0000000000000 00000000

000000: 0000000000000 00000000

Refrigeration Capacity	
Capacity on engine power -20°C	4395 W
Capacity on engine power ES400 MAX+ES400 MAX -20°C	4395 W
Capacity on engine power ES600 MAX+ES150MAX -20°C	3850 W
Capacity on engine power ES600 MAX+2 X ES150MAX -20°C	4300 W
Capacity on electrical stand by -20°C	3595 W
Capacity on electrical stand by ES400 MAX+ES400 MAX -20°C	3595 W
Capacity on electrical stand by ES600 MAX+ES150MAX -20°C	3385 W
Capacity on electrical stand by ES600 MAX+2 X ES150MAX -20°C	3595 W

Refrigeration Capacity: Individual Cooling Capacity	
Capacity on engine power ES400 MAX 0°C	5740 W
Capacity on engine power ES400 MAX -20°C	3300 W
Capacity on engine power ES600 MAX 0°C	6765 W
Capacity on engine power ES600 MAX -20°C	3460 W
Capacity on engine power ES150 MAX 0°C	3975 W
Capacity on engine power ES150 MAX -20°C	2270 W
Capacity on engine power 2 X ES150 MAX 0°C	5640 W
Capacity on engine power 2 X ES150 MAX -20°C	2995 W
Capacity on electrical stand by ES400 MAX 0°C	5300 W
Capacity on electrical stand by ES400 MAX -20°C	3010 W
Capacity on electrical stand by ES600 MAX 0°C	6305 W
Capacity on electrical stand by ES600 MAX -20°C	3110 W
Capacity on electrical stand by ES150 MAX 0°C	3850 W
Capacity on electrical stand by ES150 MAX -20°C	2165 W
Capacity on electrical stand by 2 X ES150 MAX 0°C	5045 W
Capacity on electrical stand by 2 X ES150 MAX -20°C	2705 W

Heating Capacity	
On the road	4500 W
Electric Stand By Operation	4000 W

Airflow	
ES400+ES400	1760x2 m ³ /hr
ES600 MAX+ES150MAX	2260+890 m ³ /hr
ES600 MAX++2XES150MAX	2260+(2x890) m ³ /hr

Weight	
Condenser w/o electric stand-by	100 kg
Condenser with electric stand-by	160 kg
Evaporator ES600 MAX	28 kg
Evaporator ES400 MAX	20 kg
Evaporator 2 X ES150 MAX	25 kg
Evaporator ES150 MAX	12.5 kg
Swash Plate Compressor	8.5 kg

Compressor	
Model	QP21
Displacement	215 cm ³
Number of cylinders	10

Electrical Stand by Motor	
Voltage / Phase / Frequency	400/3/50 -- 230/3/50 - -400/3/60 -- 230/3/60
Rating	8.2 kW

Refrigerant Charge	
Charge	ES400+ES400: 5.2 -- ES600+ES150: 5.0 -- ES600+2XES150: 5.15 kg

Generic (Boxlength, Refrigerant, ...)	
Box volume	40 m ³
Refrigerant	R-404A/R-452A
Airflow	1760 m ³ /hr
Controller	DSR III

Defrost	
Defrost	Automatic hot gas defrost