


**SLXi-200**
**Choose, connect, care, control**

- Lower maintenance cost through longer service intervals
- Quick temperature recovery in all ambient conditions
- Extended application flexibility
- Available as standard with R-452A low GWP refrigerant

Размеры	Установка	Конденсатор
Height	2279 mm	2279 mm
Width	2076 mm	2076 mm
Depth	537.4 mm	537.4 mm

**Технические характеристики**

Compressor	
Model	X430 C5
Displacement	492 cm <sup>3</sup>
Refrigerant Charge	
Charge	5 kg
Refrigeration Capacity	
<b>System net cooling capacity under A.T.P. conditions at 30 °C ambient</b>	
Capacity on engine power 0°C	13500 W
Capacity on engine power -20°C	7500 W
Capacity on electrical stand by 0°C	10500 W
Capacity on electrical stand by -20°C	5900 W
Generic (Boxlength, Refrigerant, ...)	
Boxlength	15 m
Refrigerant	R-452A
Controller	Smart Reefer 3
Pull down	
+20°C to -20°C (min)	160
Heating Capacity	
On the road	8000 W
Airflow	
<b>on high speed engine operation</b>	
Airflow volume @ 0 pa static pressure	5000 m <sup>3</sup> /hr
Airflow volume in fully loaded trailer	4680 m <sup>3</sup> /hr
Discharge velocity - airthrow	14 m/sec
Weight	
<b>including battery</b>	
Model 30	737 (Whisper option + 85 kg) kg
Model 50	793 (Whisper option + 85 kg) kg
Engine	
Model	TK 486V
Rating	17.9 kW
Maintenance Interval	3000 hrs
Electrical Stand by Motor	
Voltage / Phase / Frequency	400 / 3 / 50
Rating	9.3 kW

**Функции и опции**

Life cost management	
Fuel level sensor	<input type="checkbox"/> <input checked="" type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>
Data capture & communications	
TouchPrint Printer	<input checked="" type="checkbox"/>
ServiceWatch maintenance logger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
TrackKing? (tracking and load monitoring)	<input checked="" type="checkbox"/>
Wintrac (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>
Load Protection	
Air Chute	<input type="checkbox"/> <input checked="" type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
OptiSet Plus pre-set operating parameters	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/> <input checked="" type="checkbox"/>
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>
Customization	
Snow Kit dealer fitted	<input type="checkbox"/> <input checked="" type="checkbox"/>
Tail lift battery charger	<input type="checkbox"/> <input checked="" type="checkbox"/>
Whisper kit acoustic	<input type="checkbox"/>
Protection bars (ships in multiples of 3)	<input checked="" type="checkbox"/>
Low voltage disconnect	<input checked="" type="checkbox"/>
Solar Panel	<input type="checkbox"/> <input checked="" type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/> <input checked="" type="checkbox"/>
Shock Protection Bars	<input checked="" type="checkbox"/>
Ease of Use	
Kit Drop Down HMI	<input type="checkbox"/> <input checked="" type="checkbox"/>
Rear remote control SR-3	<input type="checkbox"/> <input checked="" type="checkbox"/>
Status light	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/> <input checked="" type="checkbox"/>
Fuel filtration and priming system	<input type="checkbox"/> <input checked="" type="checkbox"/>

Не применимо       Стандартная функция  
 Опция: поставляется с завода       Опция: поставляется дилером



### SLXi-300

The next generation in transport refrigeration

- Reliable operation
- Lowest emissions
- Increased shelf life
- Easier installation
- Lowest noise level
- Proven components
- Optimal data monitoring and management

## Технические характеристики

Compressor	
Model	X430 C5
Displacement	492 cm <sup>3</sup>
Refrigerant Charge	
Charge	5 kg
Refrigeration Capacity	
<b>System net cooling capacity under A.T.P. conditions at 30 °C ambient</b>	
Capacity on engine power 0°C	15000 W
Capacity on engine power -20°C	7900 W
Capacity on electrical stand by 0°C	11900 W
Capacity on electrical stand by -20°C	6200 W
Generic (Boxlength, Refrigerant, ...)	
Boxlength	15 m
Refrigerant	R-452A
Controller	Smart Reefer 3
Pull down	
+20°C to -20°C (min)	150
Heating Capacity	
On the road	12000 W
Airflow	
<b>on high speed engine operation</b>	
Airflow volume @ 0 pa static pressure	5000 m <sup>3</sup> /hr
Airflow volume in fully loaded trailer	4680 m <sup>3</sup> /hr
Discharge velocity - airthrow	14 m/sec
Weight including battery	
Model 30	737 (Whisper option + 85 kg) kg
Model 50	793 (Whisper option + 85 kg) kg
Engine	
Model	TK 486V
Rating	17.9 kW
Maintenance Interval	3000 hrs
Electrical Stand by Motor	
Voltage / Phase / Frequency	400 / 3 / 50
Rating	9.3 kW

Размеры	Установка	Конденсатор
Height	2279 mm	2279 mm
Width	2076 mm	2076 mm
Depth	537.4 mm	537.4 mm

## Функции и опции

Life cost management	
Fuel level sensor	<input type="checkbox"/> <input checked="" type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>
Data capture & communications	
TouchPrint Printer	<input checked="" type="checkbox"/>
ServiceWatch maintenance logger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
Tracking? (tracking and load monitoring)	<input checked="" type="checkbox"/>
Wintrac (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>
Load Protection	
Thermo King GDP PharmaSolutions Package	<input type="checkbox"/> <input checked="" type="checkbox"/>
OptiSet™ Plus	<input checked="" type="checkbox"/>
Produce Protection Plus (ETV & Temperature Modulation)	<input checked="" type="checkbox"/>
Air Chute	<input type="checkbox"/> <input checked="" type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
OptiSet Plus pre-set operating parameters	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/> <input checked="" type="checkbox"/>
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>
Customization	
Snow Kit dealer fitted	<input type="checkbox"/> <input checked="" type="checkbox"/>
Tail lift battery charger	<input type="checkbox"/> <input checked="" type="checkbox"/>
Whisper kit acoustic	<input type="checkbox"/>
Protection bars (ships in multiples of 3)	<input checked="" type="checkbox"/>
Low voltage disconnect	<input checked="" type="checkbox"/>
Solar Panel	<input type="checkbox"/> <input checked="" type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/> <input checked="" type="checkbox"/>
Shock Protection Bars	<input checked="" type="checkbox"/>
Ease of Use	
Kit Drop Down HMI	<input type="checkbox"/> <input checked="" type="checkbox"/>
Rear remote control SR-3	<input type="checkbox"/> <input checked="" type="checkbox"/>
Status light	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/> <input checked="" type="checkbox"/>
Fuel filtration and priming system	<input type="checkbox"/> <input checked="" type="checkbox"/>

Не применимо

Стандартная функция

Опция: поставляется с завода

Опция: поставляется дилером


**SLXi-400**
**The next generation in transport refrigeration**

- Reliable operation
- Lowest emissions
- Increased shelf life
- Easier installation
- Lowest noise level
- Proven components
- Optimal data monitoring and management

Размеры	Установка	Конденсатор
Height	2279 mm	2279 mm
Width	2076 mm	2076 mm
Depth	537.4 mm	537.4 mm

**Технические характеристики**

Compressor	
Model	X430 C5
Displacement	492 cm <sup>3</sup>
Refrigerant Charge	
Charge	5.5 kg
Refrigeration Capacity	
<b>System net cooling capacity under A.T.P. conditions at 30 °C ambient</b>	
Capacity on engine power 0°C	18700 W
Capacity on engine power -20°C	10000 W
Capacity on electrical stand by 0°C	13200 W
Capacity on electrical stand by -20°C	7100 W
Generic (Boxlength, Refrigerant, ...)	
Boxlength	16 m
Refrigerant	R-452A
Controller	Smart Reefer 3
Pull down	
+20°C to -20°C (min)	120
Heating Capacity	
On the road	13300 W
Airflow	
<b>on high speed engine operation</b>	
Airflow volume @ 0 pa static pressure	5500 m <sup>3</sup> /hr
Airflow volume in fully loaded trailer	5100 m <sup>3</sup> /hr
Discharge velocity - airthrow	16 m/sec
Weight	
<b>including battery</b>	
Model 30	737 (Whisper option + 85 kg) kg
Model 50	792 (Whisper option + 85 kg) kg
Engine	
Model	TK 486V
Rating	17.9 kW
Maintenance Interval	3000 hrs
Electrical Stand by Motor	
Voltage / Phase / Frequency	400 / 3 / 50
Rating	9.3 kW

**Функции и опции**

Life cost management	
Fuel level sensor	<input type="checkbox"/> <input checked="" type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>
Data capture & communications	
TouchPrint Printer	<input checked="" type="checkbox"/>
ServiceWatch maintenance logger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
TrackKing? (tracking and load monitoring)	<input checked="" type="checkbox"/>
Wintrac (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>
Load Protection	
Thermo King GDP PharmaSolutions Package	<input type="checkbox"/> <input checked="" type="checkbox"/>
Produce Protection Plus (ETV & Temperature Modulation)	<input checked="" type="checkbox"/>
Air Chute	<input type="checkbox"/> <input checked="" type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
OptiSet Plus pre-set operating parameters	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/> <input checked="" type="checkbox"/>
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>
Customization	
Snow Kit dealer fitted	<input type="checkbox"/> <input checked="" type="checkbox"/>
Tail lift battery charger	<input type="checkbox"/> <input checked="" type="checkbox"/>
Whisper kit acoustic	<input type="checkbox"/>
Protection bars (ships in multiples of 3)	<input checked="" type="checkbox"/>
Low voltage disconnect	<input checked="" type="checkbox"/>
Solar Panel	<input type="checkbox"/> <input checked="" type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/> <input checked="" type="checkbox"/>
Ease of Use	
Kit Drop Down HMI	<input type="checkbox"/> <input checked="" type="checkbox"/>
Rear remote control SR-3	<input type="checkbox"/> <input checked="" type="checkbox"/>
Status light	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/> <input checked="" type="checkbox"/>
Fuel filtration and priming system	<input type="checkbox"/> <input checked="" type="checkbox"/>

 Не применимо

 Стандартная функция

 Опция: поставляется с завода

 Опция: поставляется дилером



### SLXi SPECTRUM

**Ideal for multi-temperature transport**

- Multi-temperature configuration means greater vehicle utilisation
- Enhanced SR-3 controller
- Reliable operation

Размеры	Установка	Конденсатор
Height	2279 mm	2279 mm
Width	2076 mm	2076 mm
Depth	537.4 mm	537.4 mm

## Технические характеристики

Compressor	
Model	X430 C5
Displacement	492 cm <sup>3</sup>
Refrigerant Charge	
Charge	9.5 kg
Refrigeration Capacity	
<b>System net cooling capacity under A.T.P. conditions at 30 °C ambient</b>	
Capacity on engine power 0°C	19100 W
Capacity on engine power -20°C	9000 W
Capacity on electrical stand by 0°C	11200 W
Capacity on electrical stand by -20°C	6100 W
Generic (Boxlength, Refrigerant, ...)	
Boxlength	15 m
Refrigerant	R-452A
Controller	Smart Reefer 3
Heating Capacity	
On the road	12000 W
Airflow	
<b>on high speed engine operation</b>	
Airflow volume @ 0 pa static pressure	5000 m <sup>3</sup> /hr
Airflow volume in fully loaded trailer	4680 m <sup>3</sup> /hr
Discharge velocity - athrow	15 m/sec
Weight	
<b>including battery</b>	
Model 30	759 (Whisper option + 85 kg) kg
Model 50	814 (Whisper option + 85 kg) kg
Engine	
Model	TK 486V
Rating	17.9 kW
Maintenance Interval	3000 hrs
Electrical Stand by Motor	
Voltage / Phase / Frequency	400 / 3 / 50
Rating	9.3 kW

## Функции и опции

Life cost management	
Precision Temperature Control (PTC)	<input checked="" type="checkbox"/>
Fuel level sensor	<input type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>
Data capture & communications	
TouchPrint Printer	<input type="checkbox"/>
ServiceWatch maintenance logger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input type="checkbox"/>
TracKing? (tracking and load monitoring)	<input checked="" type="checkbox"/>
Wintrac (data analysis software)	<input type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>
Load Protection	
Host Zone Null	<input checked="" type="checkbox"/>
Thermo King GDP PharmaSolutions Package	<input type="checkbox"/>
Produce Protection Plus (ETV & Temperature Modulation)	<input checked="" type="checkbox"/>
Air Chute	<input type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/>
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>
Customization	
Snow Kit dealer fitted	<input type="checkbox"/>
Tail lift battery charger	<input type="checkbox"/>
Whisper kit acoustic	<input type="checkbox"/>
Protection bars (ships in multiples of 3)	<input checked="" type="checkbox"/>
Low voltage disconnect	<input checked="" type="checkbox"/>
Solar Panel	<input type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/>
Evaporator guard	<input type="checkbox"/>
Ease of Use	
Kit Drop Down HMI	<input type="checkbox"/>
Rear remote control SR-3	<input type="checkbox"/>
Status light	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/>
Fuel filtration and priming system	<input type="checkbox"/>

Не применимо       Стандартная функция  
 Опция: поставляется с завода       Опция: поставляется дилером



### SLXi-300 Whisper Pro

The next generation in transport refrigeration

- Reliable operation
- Lowest emissions
- Increased shelf life
- Easier installation
- Complies with the most stringent noise abatement standards
- Requires no manual intervention to activate or deactivate PIEK mode
- Proven components
- Optimal data monitoring and management

## Технические характеристики

### Refrigeration Capacity High Speed

Capacity on engine power 0°C	16500 W
Capacity on engine power -20°C	9400 W

### Refrigeration Capacity PIEK Mode

Capacity on engine power 0°C	10800
Capacity on engine power -20°C	6500

### Compressor

Model	X430 C5
Displacement	492 cm <sup>3</sup>

### Refrigerant Charge

Charge	5 kg
--------	------

### Refrigeration Capacity

**System net cooling capacity under A.T.P. conditions at 30 °C ambient**

Capacity on engine power 0°C	16500 W
Capacity on engine power -20°C	9400 W
Capacity on electrical stand by 0°C	10100 W
Capacity on electrical stand by -20°C	5800 W

### Generic (Boxlength, Refrigerant, ...)

Boxlength	15 m
Refrigerant	R-452A
Controller	Smart Reefer 3

### Pull down

+20°C to -20°C (min)	130
----------------------	-----

### Heating Capacity

On the road	12000 W
-------------	---------

### Airflow

**on high speed engine operation**

Airflow volume @ 0 pa static pressure	5000 m <sup>3</sup> /hr
Airflow volume in fully loaded trailer	4680 m <sup>3</sup> /hr
Discharge velocity - airthrow	14 m/sec

### Weight

**including battery**

Model 30	822 kg
Model 50	878 kg

### Engine

Model	TK 486V
Rating	17.9 kW
Maintenance Interval	3000 hrs

### Electrical Stand by Motor

Voltage / Phase / Frequency	400 / 3 / 50
Rating	9.3 kW

Размеры	Установка	Конденсатор
Height	2279 mm	2279 mm
Width	2076 mm	2076 mm
Depth	537.4 mm	537.4 mm

## Функции и опции

### Life cost management

Fuel level sensor	<input type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>

### Data capture & communications

TouchPrint Printer	<input type="checkbox"/>
ServiceWatch maintenance logger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input type="checkbox"/>
TracKing? (tracking and load monitoring)	<input checked="" type="checkbox"/>
Wintrac (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>

### Load Protection

Thermo King GDP PharmaSolutions Package	<input type="checkbox"/>
OptiSet™ Plus	<input checked="" type="checkbox"/>
Produce Protection Plus (ETV & Temperature Modulation)	<input checked="" type="checkbox"/>
Air Chute	<input type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
OptiSet Plus pre-set operating parameters	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/>
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>

### Customization

Snow Kit dealer fitted	<input type="checkbox"/>
Tail lift battery charger	<input type="checkbox"/>
Whisper kit acoustic	<input type="checkbox"/>
Protection bars (ships in multiples of 3)	<input checked="" type="checkbox"/>
Low voltage disconnect	<input checked="" type="checkbox"/>
Solar Panel	<input type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/>

### Ease of Use

Kit Drop Down HMI	<input type="checkbox"/>
Rear remote control SR-3	<input type="checkbox"/>
Status light	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/>
Fuel filtration and priming system	<input type="checkbox"/>

Не применимо

Стандартная функция

Опция: поставляется с завода

Опция: поставляется дилером



### SLXi SPECTRUM Whisper Pro

**Best in class for quiet operation thanks to noise-reduced components**

- Complies with the most stringent noise abatement standards
- Requires no manual intervention to activate or deactivate PIEK mode
- Extensive noise containment measures within the unit design

## Технические характеристики

### Refrigeration Capacity High Speed

Capacity on engine power 0°C	18400 W
Capacity on engine power -20°C	9000 W

### Refrigeration Capacity PIEK Mode

Capacity on engine power 0°C	12400
Capacity on engine power -20°C	5800

### Compressor

Model	X430 C5
Displacement	492 cm <sup>3</sup>

### Refrigerant Charge

Charge	9.5 kg
--------	--------

### Refrigeration Capacity

#### System net cooling capacity under A.T.P. conditions at 30 °C ambient

Capacity on engine power 0°C	18400 W
Capacity on engine power -20°C	9000 W
Capacity on electrical stand by 0°C	10500 W
Capacity on electrical stand by -20°C	6100 W

### Generic (Boxlength, Refrigerant, ...)

Boxlength	15 m
Refrigerant	R-452A
Controller	Smart Reefer 3

### Heating Capacity

On the road	12000 W
-------------	---------

### Airflow

#### on high speed engine operation

Airflow volume @ 0 pa static pressure	5000 m <sup>3</sup> /hr
Airflow volume in fully loaded trailer	4680 m <sup>3</sup> /hr
Discharge velocity - airthrow	15 m/sec

### Weight

#### including battery

Model 30	844 kg
Model 50	900 kg

### Engine

Model	TK 486V
Rating	17.9 kW
Maintenance Interval	3000 hrs

### Electrical Stand by Motor

Voltage / Phase / Frequency	400 / 3 / 50
Rating	9.3 kW

Размеры	Установка	Конденсатор
Height	2279 mm	2279 mm
Width	2076 mm	2076 mm
Depth	537.4 mm	537.4 mm

## Функции и опции

### Life cost management

Precision Temperature Control (PTC)	<input checked="" type="checkbox"/>
Fuel level sensor	<input type="checkbox"/>
Premium AGM battery	<input checked="" type="checkbox"/>
2-year warranty coverage	<input checked="" type="checkbox"/>
EMI 3000: Extended maintenance interval	<input checked="" type="checkbox"/>

### Data capture & communications

TouchPrint Printer	<input checked="" type="checkbox"/>
ServiceWatch maintenance logger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
TrackKing? (tracking and load monitoring)	<input checked="" type="checkbox"/>
Wintrac (data analysis software)	<input checked="" type="checkbox"/>
USB data port	<input checked="" type="checkbox"/>

### Load Protection

Host Zone Null	<input checked="" type="checkbox"/>
Thermo King GDP PharmaSolutions Package	<input type="checkbox"/>
Produce Protection Plus (ETV & Temperature Modulation)	<input checked="" type="checkbox"/>
Air Chute	<input type="checkbox"/>
Discharge Air Control Freeze protection	<input checked="" type="checkbox"/>
Door switches	<input type="checkbox"/>
Diesel/Electric Auto Switching + Auto Phase Correction	<input checked="" type="checkbox"/>

### Customization

Snow Kit dealer fitted	<input type="checkbox"/>
Tail lift battery charger	<input type="checkbox"/>
Whisper kit acoustic	<input type="checkbox"/>
Protection bars (ships in multiples of 3)	<input checked="" type="checkbox"/>
Low voltage disconnect	<input checked="" type="checkbox"/>
Solar Panel	<input type="checkbox"/>
Fuel Tank (Plastic 230L or Aluminium 190L)	<input type="checkbox"/>
Evaporator guard	<input type="checkbox"/>

### Ease of Use

Kit Drop Down HMI	<input type="checkbox"/>
Rear remote control SR-3	<input type="checkbox"/>
Status light	<input checked="" type="checkbox"/>
Triple Combo Display (Fuel, Alarms, Temperature indications)	<input type="checkbox"/>
Fuel filtration and priming system	<input type="checkbox"/>

Не применимо

Стандартная функция

Опция: поставляется с завода

Опция: поставляется дилером